



PURPOSE:

- Designed for heavy-duty use in commercial and industrial applications, like fence installation, highway departments / municipalities for repairing guardrails and installing pilings. Pole building companies for the initial pole installation.

FEATURES:

- Include universal skid steer mount, top link, hoses and flat-faced couplers
- High torque planetary-reduction drive
- Easy hookup, no third drain line required
- Heat treated drive shafts for durability
- Auger drive unit and bits in 2-9/16" round or 2" hex shafts
- EDGE bits from 4" to 48" sold separately. A wide variety is available from standard bits to rock conical. Extensions are also available from 14" to 48"



SPECIFICATIONS:

	Model	Weight (lbs/kg)	Hyd. Req. (gpm/lpm)	Max. Auger Dia. (in/mm)	Speed (rpm)	Theo. Torque (lbs. ft/Nm)	Available for purchase with wholegood
2-9/16" Round	PA150	340/154	10-20/38-76	30/762	103 @ 20 gpm	1783/2417 @ 3000 psi	
	PA210	345/156	16-30/61-114	36/914	104 @ 30 gpm	2562/3473 @ 3000 psi	×
	PA230	347/157	18-30/68-114	48/1219	81 @ 30 gpm	2998/4065 @ 3000 psi	
2" Hex	PA150H	340/154	10-20/38-76	30/762	103 @ 20 gpm	1783/2471 @ 3000 psi	
	PA210H	345/156	16-30/61-114	36/914	104 @ 30 gpm	2562/3473 @ 3000 psi	×
	PA230H	347/157	18-30/68-114	48/1219	81 @ 30 gpm	2998/4065 @ 3000 psi	

MACHINE COMPATIBILITY:

	Radial Skid Loaders							Vertical Skid Loaders			Track Loaders					
	R105/1050R/1050 R	R135/1350R/1350 R	R150/1500R/1500 R	R165/1650R/1650 R	R190/1900R/1900 R	R220/2200R/2200 R	R260/2600R/2600 R	V270/2700V/2700 V	V330/3300V/3000 V	V420/4200V/4200 V	RT105/1050RT/1050 RT	RT135/1350RT/1350 RT	RT165/1650RT/1650 RT	RT185/1850RT/1850 RT	RT215/2150RT/2150 RT	RT255/2550RT/2550 RT
PA150	×	×	×	×	×					×	×	×				
PA210		×	×	×	×	×	×	×	×		×	×	×	×	×	×
PA230				×	×	×	×	×	×			×	×	×	×	×
PA150H	×	×	×	×	×					×	×	×				
PA210H		×	×	×	×	×	×	×	×		×	×	×	×	×	×
PA230H				×	×	×	×	×	×			×	×	×	×	×

*Note: Machine compatibility is based on operating capacity of the machine and the weight of the attachment