

# V230

SKID LOADER



## KEY FEATURES

- **NEW** Color Display with Keyless Start + Security Code
- **NOW STANDARD** Pilot Joystick Controls
- **NEW** Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- **NEW** LED Work, LED Rear Lights + Egress Lighting
- Vertical Lift Arm for More Reach at Dump Height
- **NOW STANDARD** Hydraglide™ Ride Control
- **NEW** Greasable Pins for Reduced TCO
- Flip-Up Cooler with Hydraulic Fan
- **NOW STANDARD** Backup Alarm

# V230 SKID LOADER



## SPECIFICATIONS

	METRIC	IMPERIAL
Operating Weight	7710 lbs	3497 kg
Overall Operating Height - Fully Raised	159"	4039 mm
Height to Hinge Pin - Fully Raised	121.5"	3086 mm
Overall Height to Top of ROPS	81"	2058 mm
Dump Angle at Full Height	42°	
Dump Height - Fully Raised	91"	2312 mm
Rollback Angle Fully Raised	92°	
Overall Length with Bucket	141.3"	3589 mm
Dump Reach at Full Height	32.5"	826 mm
Rollback Angle at Ground	29°	
Seat to Ground Height	38.5"	978 mm
Crawler Base	43"	1092 mm
Overall Width - Less Bucket	67.2"	1707 mm
Ground Clearance to Chassis	8"	203 mm
Overall Length without Bucket	109.8"	2789 mm
Specified Height	87"	2210 mm
Reach at Specified Height	34.5"	876 mm
Departure Angle	25°	
Clearance Radius - Front with Bucket	85.5"	2171 mm
Clearance Radius - Front without Bucket	51.5"	1308 mm
Clearance Radius - Rear	66.5"	1689 mm
Bucket Width	70"	1778 mm
Standard Tire Width	12 x 16.5	
Operating Capacity at 50% Tipping Load	2300 lbs	1043 kg
Operating Capacity at 50% Tipping Load with Optional Side Weights	2450 lbs	1111 kg
Make / Model	Yanmar / 4TNV98CT-XNGL	
Type	Stage 5	
Gross Power	72 HP	53.7 kW
Net Power	70.7 HP	52.7 kW
Maximum Torque @ 1800 rpm	217 ft/lbs	294 Nm
Battery	12 V	3.0 kW
Travel Speed	7.9 mph	12.7 km/hr
Travel Speed with 2-Speed Option	12.6 mph	20 km/hr

WEIGHT - DIMENSIONS

CAPACITIES

ENGINE

PERFORMANCES

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

## STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- NEW Back-Up Alarm
- NEW Battery Disconnect
- Brake Control (Auto/Manual)
- NEW Color Display with Keyless Start + Security Code
- NEW Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Hand Throttle
- Foot Throttle / NEW Deceleration Pedal
- High-Back Adjustable Seats
- Horn
- Hydraloc™ Safety System
- NEW Hydraglide™ Ride Control
- NEW Hydraulic Variable Speed Fan
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- NEW LED Tail + Work Lights
- NEW Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- Flip-up Cooler
- 12-Volt + USB Charging Ports
- One Speed Drive
- Slope Roof
- Greasable Cab
- Manual Attach
- 4-Point Lift

## OPTIONAL FEATURES

- 14-Pin Attachment Control
- Air Conditioning + Heating with Cab Enclosure
- Bluetooth Hands-Free Radio
- Cast Rear Bumper
- NEW Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- NEW Impact Side Windows
- NEW LED Road Light Package
- NEW LED Side Lights
- FOPS Level II with Light Guard
- Rear Window Wiper
- Rearview Camera
- Rearview Mirror
- NEW Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Side Counterweights
- Suspension Seat - Air Ride or Mechanical
- NEW Cloth, Heated Seat with Air Suspension + Extended Backrest
- Two-Speed Drive
- 4-Way Flashers
- Sliding Side Windows



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517