

# VT210

TRACK LOADER

GEHL®



## KEY FEATURES

- **NEW** Color Display with Keyless Start + Security Code
- IdealTrax™ Auto Tensioning System
- **NEW** Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- **NEW** LED Work, LED Rear Lights + Egress Lighting
- Vertical Lift Arm for More Reach at Dump Height
- **NOW STANDARD** Hydraglide™ Ride Control
- **NEW** Dual Flange Idlers - Front + Rear
- **NOW STANDARD** Pilot Joystick Controls
- **NOW STANDARD** Backup Alarm

WWW.GEHL.COM



# VT210 TRACK LOADER



## SPECIFICATIONS

	IMPERIAL	METRIC
Operating Weight	8865 lbs	4021 kg
Overall Operating Height - Fully Raised	158.5"	4026 mm
Height to Hinge Pin - Fully Raised	121"	3073 mm
Overall Height to Top of ROPS	80.5"	2045 mm
Dump Angle at Full Height	42°	
Dump Height - Fully Raised	90.5"	2300 mm
Rollback Angle Fully Raised	92°	
Overall Length with Bucket	139.5"	3543 mm
Dump Reach at Full Height	36.5"	927 mm
Rollback Angle at Ground	29°	
Seat to Ground Height	38"	965 mm
Crawler Base	54.5"	1384 mm
Overall Width - Less Bucket	65.9"	1674 mm
Ground Clearance to Chassis	7.5"	191 mm
Overall Length without Bucket	108"	2743 mm
Specified Height	86.5"	2197 mm
Reach at Specified Height	38.5"	978 mm
Departure Angle	30°	
Clearance Radius - Front with Bucket	87"	2210 mm
Clearance Radius - Front without Bucket	54"	1374 mm
Clearance Radius - Rear	63"	1600 mm
Bucket Width	66"	1676 mm
Standard Track Width	12.6"	320 mm
Operating Capacity at 35% Tipping Load	2100 lbs	952 kg
Operating Capacity at 35% Tipping Load with Side Weights	2200 lbs	998 kg
Operating Capacity at 50% Tipping Load	3000 lbs	1361 kg
Operating Capacity at 50% Tipping Load with Optional Side Weights	3150 lbs	1429 kg
Make / Model	Yanmar / 4TNV98C-NGL	
Type	Stage 5	
Gross Power	69.3 HP	51.7 kW
Net Power	68.4 hp	51 kW
Maximum Torque @ 1625 rpm	178 ft/lbs	241 Nm
Battery	12 V	3.0 kW
Travel Speed	6.4 mph	10.3 km/hr
Travel Speed with 2-Speed Option	9.5 mph	15.3 km/hr
Tractive Effort	9141 lbs	4146 kg

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

## STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- NEW Battery Disconnect
- Brake Control (Auto/Manual)
- NEW Color Display with Keyless Start + Security Code
- NEW Dual Flange Idlers - Front + Rear
- NEW Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- High-Back Adjustable Seats
- IdealTrax™ Auto Tensioning System
- Flip-Up Cooler
- Foot Throttle / NEW Deceleration Pedal
- Hand Throttle
- Horn
- Hydraloc™ Safety System
- Hydraglide™ Ride Control
- NEW Hydraulic Variable Speed Fan
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- NEW LED Tail + Work Lights
- NEW Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- 12-Volt + USB Charging Ports
- Two Speed Drive
- Sloped Roof
- Greasable Pins
- Manual Attach
- 4-Point Lift
- Sound Reduction Package

## OPTIONAL FEATURES

- 14-Pin Attachment System
- Air Conditioning in Cab Enclosure
- Bluetooth Hands-Free Radio
- Cab Enclosure
- Cast Rear Bumper
- Side Counterweights
- NEW Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- NEW Impact Side Windows
- NEW LED Road Light Package
- NEW LED Side Lights
- FOPS Level II with Light Guard
- Rearview Camera
- Rearview Mirror
- NEW Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Suspension Seat - Air Ride or Mechanical
- NEW Cloth, Heated Seat with Air Suspension and Extended Backrest
- 4-Way Flashers
- Sliding Side Windows



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517