

# VT230

TRACK LOADER



## KEY FEATURES

- **NEW** Color Display with Keyless Start + Security Code
- IdealTrax™ Auto Tensioning System
- **NEW** Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- **NEW** LED Work, LED Rear Lights + Egress Lighting
- Vertical Lift Arm for More Reach at Dump Height
- **NOW STANDARD** Hydraglide™ Ride Control
- **NEW** Dual Flange Idlers - Front + Rear
- **NOW STANDARD** Pilot Joystick Controls
- **NOW STANDARD** Backup Alarm

\*Optional features

# VT230 TRACK LOADER



## SPECIFICATIONS

	IMPERIAL	METRIC	
WEIGHT + DIMENSIONS	Operating Weight	9250 lbs	4196 kg
	Overall Operating Height - Fully Raised	158.5"	4026 mm
	Height to Hinge Pin - Fully Raised	121"	3073 mm
	Overall Height to Top of ROPS	80.5"	2045 mm
	Dump Angle at Full Height	42°	
	Dump Height - Fully Raised	90.5"	2300 mm
	Rollback Angle Fully Raised	92°	
	Overall Length with Bucket	141.3"	3589 mm
	Dump Reach at Full Height	36.5"	927 mm
	Rollback Angle at Ground	29°	
	Seat to Ground Height	38"	965 mm
	Crawler Base	54.5"	1384 mm
	Overall Width - Less Bucket	69"	1753 mm
	Ground Clearance to Chassis	7.5"	191 mm
	Overall Length without Bucket	109.8"	2789 mm
	Specified Height	86.5"	2197 mm
	Reach at Specified Height	38.5"	978 mm
	Departure Angle	28°	
	Clearance Radius - Front with Bucket	88"	2235 mm
	Clearance Radius - Front without Bucket	54"	1374 mm
Clearance Radius - Rear	64"	1625 mm	
Bucket Width	70"	1778 mm	
Standard Track Width	12.6"	320 mm	
CAPACITIES	Operating Capacity at 35% Tipping Load	2300 lbs	1043 kg
	Operating Capacity at 35% Tipping Load with Side Weights	2400 lbs	1089 kg
	Operating Capacity at 50% Tipping Load	3286 lbs	1490 kg
	Operating Capacity at 50% Tipping Load with Optional Side Weights	3436 lbs	1559 kg
ENGINE	Make / Model	Yanmar / 4TNV98CT-XNGL	
	Type	Stage 5	
	Gross Power	72 HP	53.7 kW
	Net Power	70.7 HP	52.7 kW
	Maximum Torque @ 1800 rpm	217 ft./lbs	294 Nm
Battery	12 V	3.0 kW	
PERFORMANCES	Travel Speed	6.4 mph	10.3 km/hr
	Travel Speed with 2-Speed Option	9.5 mph	15.3 km/hr
	Tractive Effort	9126 lbs	4139 kg

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

## STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- NEW Battery Disconnect
- Brake Control (Auto/Manual)
- NEW Color Display with Keyless Start + Security Code
- NEW Dual Flange Idlers - Front + Rear
- NEW Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- High-Back Adjustable Seats
- IdealTrax™ Auto Tensioning System
- Flip-Up Cooler
- Foot Throttle / NEW Deceleration Pedal
- Hand Throttle
- Horn
- Hydraloc™ Safety System
- Hydraglide™ Ride Control
- NEW Hydraulic Variable Speed Fan
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- NEW LED Tail + Work Lights
- NEW Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- 12-Volt + USB Charging Ports
- Two Speed Drive
- Sloped Roof
- Greasable Pins
- Manual Attach
- 4-Point Lift
- Sound Reduction Package

## OPTIONAL FEATURES

- 14-Pin Attachment System
- Air Conditioning in Cab Enclosure
- Bluetooth Hands-Free Radio
- Cab Enclosure
- Cast Rear Bumper
- Side Counterweights
- NEW Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- NEW Impact Side Windows
- NEW LED Road Light Package
- NEW LED Side Lights
- FOPS Level II with Light Guard
- Rearview Camera
- Rearview Mirror
- NEW Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Suspension Seat - Air Ride or Mechanical
- NEW Cloth, Heated Seat with Air Suspension and Extended Backrest
- 4-Way Flashers
- Sliding Side Windows



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517